



P/N	L/(M)	T/(MM)
26-0150MM	15	200
26-0200MM	20	250
26-0250MM	25	300
26-0300MM	30	350
26-0500MM	50	600

NOTES:

- 1:100% short,open and miss wire test.
- 2:Cable marking:CONNEKT GEAR AWM STYLE 2919 80°C 30V LOW VOLTAGE Computer Cable RoHS & REACH Compliant

PIN OUT

P1	P2	P1	P2
1	Red coax conductor	9	9
2	Green coax conductor	10	10
3	Blue coax conductor	11	11
4		12	12
5		13	13
6	Red coax drain	14	14
7	Green coax drain	15	15
8	Blue coax drain	8	shell Drain shell

⑥	FERRITE CORE	F5B:RH14.2*28.5*9.5	2	PCS
⑤	OUTER MOULDED	BLACK 45P PVC	0.048	KG
④	INNER MOULDED	LDPE	0.021	KG
③	SCREW	#4-40UNC 2.3*45.5MM,BLACK PVC	4	PCS
②	CONNECTOR	HDB 15PIN/MALE,BLUE INSULATOR,NICKEL PLATED SHELL,GOLD PLATED PIN,	2	PCS
①	CABLE	(1C*7/0.12BC+FFPE+D 7/0.12BC+AL+PVC)*3C+9C*7/0.12BC+AL+D 7/0.12BC+BRAID(80/0.12 ALM). JACKET:BLACK PVC. OD:8.0±0.2MM	L	M
NO.	MATERIAL	DESCRIPTION	QTY.	UNIT

Ltemref	Quantity	Title/Name,designation,material,dimension etc			Article No./Reference	
Designed by	Checked by	Approved by - date	File name	Date	Scale	
		JUL 27.2015		JUL 27.2015	FREE	
ANGLE:				VGA(3+9),HDB15M-HDB15M,28AWG,BLACK		
UNIT:MM				26-0150MM,26-0200MM	Edition	Sheet
				26-0250MM,26-0300MM,26-0500MM	1	1/1