


P/N	L/(M)	T/(MM)
26-1666	2	30
26-1667	3	45

NOTES:

- 1:100% short,open and miss wire test.
- 2:Cable marking:CONNEkT GEAR AWM STYLE 2919 80℃ 30V LOW VOLTAGE Computer Cable RoHS & REACH Compliant



NO.	MATERIAL	DESCRIPTION	QTY.	UNIT
⑥	OUTER MOULDED	BLACK 45P PVC	0.048	KG
⑤	INNER MOULDED	LDPE	0.021	KG
④	SCREW	#4-40UNC 2.3*45.5MM,BLACK PVC	4	PCS
③	CONNECTOR	DVI 24+5/M BLACK INSULATOR,NICKEL PLATED SHELL,GOLD PLATED PIN	1	PCS
②	CONNECTOR	HDB15PIN/M BLUE INSULATOR,NICKEL PLATED SHELL,GOLD PLATED PIN	1	PCS
①	CABLE	(1C*7/0.1BC+FPE+D+PVC)*3C+9C*7/0.10BC+AL+D+B,JACKET:BLACK PVC, OD:8.0±0.2MM	L	M

Ltemref	Quantity	Title/Name,designation,material,dimension etc	Article No./Reference		
Designed by	Checked by	Approved by - date JUL 27.2015	File name	Date JUL 27.2015	Scale FREE
ANGLE:			VGA to DVI-I Monitor Cable,BLACK		
UNIT:MM			26-1666,26-1667	Edition 1	Sheet 1/1