



P/N	L/m	T/mm
26-2934	m	20
26-2935	100	30
26-2936	0	50
200		
0		
300		
0		

NOTES:

1.OPEN/SHORT/INTERMITTENCE:100%.

2. INSULATION RESISTANCE:DC 300V 0.01S 10MΩMin

3.CONDUCTIVE RESISTANCE:5ΩMax

4.ROHS & REACH COMPLIANT

PIN OUT	
P1	P2
1	A4
2	A7
3	A6
4	A12
SHELL	DRAIN A12

⑤	MOLDED	45P BLACK PVC		G	LtemrefQuantityTitle/Name,designation,material,dimension etcArticle NO./Reference Designed byCheckde byApproved by - dateFile nameDateScale			
④	MOLDED	LDPE		G				
③	CONNECTOR	TYPE C MALE,GOLD PLATED PIN,BLACK INSULATION,NICKEL PLATED SHELL+R=5.1KΩ	1	PCS	2026.08.21			
②	CONNECTOR	USB2.0 B MALE,GOLD PLATED PIN,WHITE INSULATION,NICKEL PLATED SHELL	1	PCS				
①	CABLE	7/0.10TC*1P+7/0.20TC*2C+AL+D(7/0.12BC)+B(4*16/0.12AL-MG),BLACK PVC JACKET, OD:4.0±0.2mm MARKING: USB 2.0 CABLE AWM 2725 80°C 30V VW-1	L	MM	ANGLE:  USB2.0 TYPE C-USB BM			
NO.	MATERIAL	DESCRIPTION	QTY.	UNIT	UNIT:MM			
					26-293X		Edition Sheet 1 1/1	