



NOTES:

- 1:100% short,open and miss wire test.
- 2:Cable marking:AWM 80°C 30V VW-1  
USB 3.0 SUPER SPEED CABLE
- 3:ROHS & REACH Compliant

⑤	OUTER MOULDED	BLUE 45P PVC	0.021	KG
④	INNER MOULDED	LEPD	0.010	KG
③	CONNECTOR	USB3.0 B TYPE/MALE,BLUE INSULATOR,NICKEL PLATED SHELL,GOLD PLATED PIN,	1	PCS
②	CONNECTOR	USB3.0 A TYPE/MALE,BLUE INSULATOR,NICKEL PLATED SHELL,GOLD PLATED PIN,	1	PCS
①	CABLE	(1P*7/0.12BC+D+AL+MYLAR)*2C+1P*7/0.12BC+2C*7/0.12BC+AL+D+B, JACKET:BLUE PVC,OD:5.5±0.2MM	2000	MM
NO.	MATERIAL	DESCRIPTION	QTY.	UNIT

Ltemref	Quantity	Title/Name,designation,material,dimension etc	Article No./Reference		
Designed by	Checked by	Approved by - date JUL 27.2015	File name	Date JUL 27.2015	Scale FREE
ANGLE:			USB 3.0 connection cable ,AM-BM,BLUE		
UNIT:MM			26-2952	Edition 1	Sheet 1/1